

View Online at <https://aerobasegroup.com/nsn/5935-00-201-2411>

Body Style:

T-shape

Overall Length:

1.281 inches

Overall Height:

1.094 inches

Overall Width:

0.562 inches

Environmental Protection:

Moisture resistant and shock proof and thermal shock resistant and vibration resistant

Mating End Quantity:

3

Contact Position Arrangement Style:

Bnc all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

4000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet latch and bayonet pin and bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 3rd mating end all contact groupings

Test Data Document:

81349-mil-c-71 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-71 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0