

View Online at <https://aerobasegroup.com/nsn/5935-00-201-2411>

**Body Style:**

T-shape

**Overall Length:**

1.281 inches

**Overall Height:**

1.094 inches

**Overall Width:**

0.562 inches

**Environmental Protection:**

Moisture resistant and shock proof and thermal shock resistant and vibration resistant

**Mating End Quantity:**

3

**Contact Position Arrangement Style:**

Bnc all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends all contact groupings

**Contact Maximum Frequency Rating:**

4000.0 megahertz all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and bayonet pin and bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Coaxial socket 3rd mating end all contact groupings

**Test Data Document:**

81349-mil-c-71 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-71 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0