Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-2482

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.938 inches
Overall Height:
Between 2.469 inches and 2.531 inches
Overall Width:
Between 2.469 inches and 2.531 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.168 inches and 0.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.933 inches and 1.943 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.933 inches and 1.934 inches
Distance From Mounting Shoulder To Front Face:
Between 0.875 inches and 0.906 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-7 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



## **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 16 **Thread Size:** 2.250 inches **Terminal Location:** Back all mating ends all contact groupings **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end 2nd contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 7 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end 2nd contact grouping **Thread Series Designator:** Nptf **Specification Data:** 81349-mil-c-5015 professional/industrial association specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0

---