NSN 5935-00-201-2857

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-2857 **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.109 inches **Overall Height:** Between 1.297 inches and 1.328 inches **Overall Width:** Between 1.297 inches and 1.328 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.120 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.963 inches and 0.973 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.963 inches and 0.973 inches **Distance From Mounting Shoulder To Front Face:** Between 0.422 inches and 0.453 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-65 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet shell **Terminal Location:** Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

NSN 5935-00-201-2857

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Shell Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Insert Material Specification:** Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 7 single mating end 1st contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.011 gold grains, troy and 0.011 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0

Mil-m-14 spec.

Mil-std (military Standard):