

View Online at <https://aerobasegroup.com/nsn/5935-00-201-3089>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.750 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

N all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 all mating ends all contact groupings

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thread Qty Per Inch (tpi):**

18 and 24

**Thread Size:**

1.125 inches and 0.625 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Silver all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Material Specification:**

Qq-c-530, comp ht federal specification single material response all mating ends single contact grouping

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 all mating ends all contact groupings

**Included Contact Type:**

Coaxial socket 2nd mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces and shell surface silver

**Precious Material And Weight:**

0.110 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0