

View Online at <https://aerobasegroup.com/nsn/5935-00-201-3089>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.750 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends all contact groupings

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Qty Per Inch (tpi):

18 and 24

Thread Size:

1.125 inches and 0.625 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Material Specification:

Qq-c-530, comp ht federal specification single material response all mating ends single contact grouping

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 all mating ends all contact groupings

Included Contact Type:

Coaxial socket 2nd mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces and shell surface silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0