Electrical Receptacle Connector - Page 1 of 2

of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-3256

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.938 inches
Overall Height:
Between 1.594 inches and 1.656 inches
Overall Width:
Between 1.594 inches and 1.656 inches
Environmental Protection:
Moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.245 inches and 1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.245 inches and 1.255 inches
Distance From Mounting Shoulder To Front Face:
Between 0.750 inches and 0.828 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1 Contact Register Arrangement Style:
Contact Position Arrangement Style:
22-14 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



# **Connector Locking Method:**

Externally threaded shell

# Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

## Thread Size:

1.375 inches

## **Terminal Location:**

Back all mating ends all contact groupings

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping and qq-s-365 federal specification

single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well all mating ends all contact groupings

#### Shell Material:

Copper alloy

Shell Surface Treatment:

Cadmium

#### Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### Included Contact Quantity:

19 single mating end single contact grouping

#### Bushing Accommodation Hole Shape:

Round

#### Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surface gold and contact surface silver

#### Precious Material:

Gold and silver

#### **Thread Series Designator:**

Unef

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.