Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-4380

### Thread Direction:

Right-hand

#### **Body Style:**

Straight shape, external coupling

### Threaded Device Type:

Coupling facility

### Mating End Quantity:

1

# Contact Removability:

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

30.0 single mating end single contact grouping

# Shell Type:

Solid

### Connector Locking Method:

### Externally threaded shell

### Thready Qty Per Inch (tpi):

6

### Thread Size:

1.313 inches

### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping or silver single mating end single contact grouping

#### **Insert Material:**

Plastic phenolic single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Steel

# Included Contact Quantity:

3 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold and contact surfaces silver

# **Precious Material And Weight:**

 $0.015\ \text{gold}\ \text{grains},\ \text{troy}\ \text{and}\ 0.015\ \text{silver}\ \text{grains},\ \text{troy}$ 

# Precious Material:

Gold and silver

Electrical Receptacle Connector - Page 2 of 2



**Thread Series Designator:** 

Uns

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0