

View Online at <https://aerobasegroup.com/nsn/5935-00-201-4382>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Thru-hole mount w/lockin

Overall Length:

1.015 inches

Bushing Diameter:

0.875 inches

Overall Diameter:

1.031 inches

Distance From Mounting Shoulder To Rear Face:

0.656 inches

Mounting Facility Thickness:

0.359 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

10-6 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Latch

Thread Length:

0.219 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.875 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end all contact groupings

Included Contact Quantity:

5 single mating end 2nd contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.006 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A039b0