Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-5197

# Thread Class:

2a

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape, external coupling

#### **Overall Length:**

1.625 inches

#### **Overall Height:**

1.266 inches

#### **Overall Width:**

1.625 inches

#### **Environmental Protection:**

Salt water resistant

#### **Unthreaded Mounting Hole Diameter:**

## 0.120 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

## Distance From Mounting Shoulder To Front Face:

0.750 inches

## Threaded Device Type:

Hub

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

22-14 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

#### Shell Type:

Solid



**Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 19 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0