NSN 5935-00-201-7933

Thread Class:

Right-hand
Body Style:
Straight shape
Overall Length:
1.562 inches
Overall Height:
0.781 inches
Overall Width:

Thread Direction:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-7933

| 0.438 inches |
|--|
| Unthreaded Mounting Hole Diameter: |
| 0.112 inches |
| Distance Between Mounting Facility Centers: |
| 1.250 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 20 20-20 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 1800.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Screw lock pin |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-19833, type gdi-30 military specification single material response single mating end |
| |
| |
| |

NSN 5935-00-201-7933

Electrical Receptacle Connector - Page 2 of 2



| Included Contact | Quantity: |
|------------------|-----------|
|------------------|-----------|

20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.