## NSN 5935-00-201-8440

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-8440 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Diameter:** Between 0.542 inches and 0.552 inches **Environmental Protection:** Pressure proof **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-2 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet latch Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Silver **Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/double flat

## NSN 5935-00-201-8440

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Shell surface silver
Precious Material And Weight:
0.100 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0