NSN 5935-00-201-8470

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-8470 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape **Overall Length:** Between 2.797 inches and 2.922 inches **Overall Height:** 3.406 inches **Overall Width:** Between 2.484 inches and 2.516 inches **Cable Entrance Diameter:** Between 1.172 inches and 1.203 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** lk-30 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): **Thread Size:** 2.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-201-8470Electrical Plug Connector - Page 2 of 2



| Contact Surface Treatment: |
|--|
| Silver single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 30 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.030 gold grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |