

View Online at <https://aerobasegroup.com/nsn/5935-00-201-9303>

Thread Direction:

Right-hand and right-hand

Overall Length:

2.656 inches

Bushing Diameter:

1.750 inches

Overall Diameter:

3.188 inches

Environmental Protection:

Pressure proof and corrosion resistant

Threaded Device Type:

Coupling facility and hub

Mating End Quantity:

1

Contact Maximum Current Rating In Amps:

41.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 2nd contact grouping

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.750 inches and 1.750 inches

Insert Material:

Plastic single mating end

Shell Material:

Aluminum alloy

Included Contact Quantity:

6 single mating end 1st contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

Polarized; built in by pass capacitors, 2000 mmfd plus or minus 20 percent on all pins; dim excl terminals

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0