NSN 5935-00-201-9420

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-201-9420

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.969 inches |
| Overall Height: |
| 0.875 inches |
| Overall Width: |
| 0.562 inches |
| Distance Between Mounting Facility Centers: |
| Between 2.945 inches and 2.961 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 300.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Thread Length: |
| 0.250 inches |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Glass single mating end and plastic acrylic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Included Contact Quantity: |
| 27 single mating end single contact grouping |
| Included Contact Type: |

meradea Contact Type

Round socket single mating end single contact grouping

NSN 5935-00-201-9420

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.027 gold grains, troy and 0.027 silver grains, troy Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A039b0