Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-203-5636

## Body Style:

Straight edge type w/mounting flange

## **Overall Length:**

4.290 inches

## **Overall Height:**

0.505 inches

## **Overall Width:**

Between 0.242 inches and 0.248 inches

## **Environmental Protection:**

Shock resistant and vibration resistant and humidity resistant and corrosion resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.096 inches and 0.101 inches

## **Distance Between Mounting Facility Centers:**

3.965 inches

## **Board Accommodated Length:**

3.300 inches single board

#### **Board Accommodated Width:**

Between 0.070 inches and 0.074 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Connector Locking Method:**

Friction

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping



### **Insert Material Specification:**

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end or mil-m-24519, ty gpt-30f military specification single material response single mating end or mil-p-46174, cl 40, grade e military specification single material response single mating end **Included Contact Quantity:** 

90 single mating end single contact grouping

#### Included Contact Type:

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

#### **Precious Material And Weight:**

0.090 gold grains, troy

#### **Precious Material:**

Gold

#### Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-55302/23 government specification

Shelf Life:

N/a

## Unit Of Measure:

Demilitarization:

No

--

Fiig:

#### A039b0

Mil-std (military Standard):

Mil-g-45204 spec.