

View Online at <https://aerobasegroup.com/nsn/5935-00-203-5649>

Overall Length:

Between 1.618 inches and 1.642 inches

Overall Width:

0.248 inches

Unthreaded Mounting Hole Diameter:

0.098 inches

Distance Between Mounting Facility Centers:

1.340 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.