Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-203-5765

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, thru-hole mount, external coupling
Overall Length:
1.675 inches
Overall Diameter:
Between 1.734 inches and 1.766 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
Between 0.691 inches and 0.722 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.125 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
18-32 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
136.0
Shell Type:
Potting
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Potting type
Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

32 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3124 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.