## NSN 5935-00-204-5125

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-204-5125 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.464 inches **Overall Height:** 1.094 inches **Overall Width:** 0.531 inches **Distance Between Mounting Facility Centers:** 2.113 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end

**Terminal Type:**Crimp single matir

Crimp single mating end single contact grouping

**Included Contact Quantity:** 

14 single mating end single contact grouping

## NSN 5935-00-204-5125

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.014 silver grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0