

View Online at <https://aerobasegroup.com/nsn/5935-00-204-6389>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape quick connect

Overall Length:

1.125 inches

Overall Width:

0.595 inches

Environmental Protection:

Pressure proof

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Mb 2nd mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene single mating end

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Included Contact Quantity:

1 2nd mating end all contact groupings

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact surface and body surface silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-f-14072 spec.