Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-204-6505

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling strain relief
Overall Length:
2.750 inches
Overall Height:
1.500 inches
Overall Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-7 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
22.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Detent



Connector Cable Strain Relief Method: Cable clamp **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end all contact groupings **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Included Contact Quantity:** 4 single mating end all contact groupings Included Contact Type: Round pin single mating end all contact groupings **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0
