NSN 5935-00-204-7343

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-204-7343 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Green **Body Style:** Threaded bushing mounted **Overall Length:** Between 0.922 inches and 1.000 inches **Mounting Bushing Length:** Between 0.375 inches and 0.438 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 2000.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.079 inches and 0.081 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** 5.0 **Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.250 inches **Criticality Code Justification:** Feat **Terminal Type:** Turret **Special Features:** Item must comply with requirements of defense electronics supply center production standard no. L00166 Material:

Plastic, polypropylene cap

NSN 5935-00-204-7343

Tip Jack - Page 2 of 2



| Material: |
|---|
| Plastic polyamide insulator |
| Precious Material And Location: |
| Terminal and spring contact surfaces gold |
| Surface Treatment: |
| Gold terminal |
| Surface Treatment: |
| Gold spring |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A03400