## NSN 5935-00-204-7685

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-204-7685
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.172 inches and 1.266 inches
Overall Height:
Between 1.359 inches and 1.391 inches
Overall Width:
Between 1.359 inches and 1.391 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.033 inches and 1.043 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.033 inches and 1.043 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sk-u4 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
10.0 single mating end 2nd contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
6
Thread Size:
1.312 inches
Terminal Location:

Tommar Location

Back single mating end all contact groupings

## NSN 5935-00-204-7685

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
3 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end 2nd contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.004 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A039b0