

View Online at <https://aerobasegroup.com/nsn/5935-00-204-9510>

**Thread Class:**

2b

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

1.719 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Cable Entrance Diameter:**

0.781 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Cable End:**

2.125 inches

**Thread Size:**

1.500 inches

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

16 single mating end single contact grouping

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0