NSN 5935-00-211-1961

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-211-1961

| view Online at https://aerobasegroup.com/hsn/5955-00-211-196 |
|---|
| Body Style: |
| Straight shape, internal coupling w/strain relief |
| Overall Diameter: |
| 1.777 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration resistant |
| Cable Entrance Diameter: |
| Between 0.918 inches and 0.958 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 25.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 46.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 31 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Shelf Life: |

Demilitarization:

Unit Of Measure:

No

N/a

NSN 5935-00-211-1961

Electrical Plug Connector - Page 2 of 2



Fiig:

A039b0