# NSN 5935-00-211-1964

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-211-1964

<b>Body</b>	Stv	-ما
DUUV	OLV.	ıc.

Straight shape, internal coupling w/strain relief

**Overall Diameter:** 

1.777 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Cable Entrance Diameter:** 

Between 0.918 inches and 0.958 inches

**Mating End Quantity:** 

1

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

25.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

240.0

Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

# **Connector Cable Strain Relief Method:**

Cable clamp

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

**Insert Material:** 

Rubber single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

#### **Included Contact Quantity:**

31 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

Shelf Life:

N/a

## **Unit Of Measure:**

--

# NSN 5935-00-211-1964

Electrical Plug Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0