NSN 5935-00-211-2258

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-211-2258

Body Style:
Straight shape
Overall Length:
0.935 inches
Overall Height:
0.915 inches
Overall Width:
0.305 inches
Environmental Protection:
Pressure proof and heat resistant and moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.084 inches and 0.094 inches
Distance Between Mounting Facility Centers:
Between 0.705 inches and 0.725 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"2, 15" single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate

NSN 5935-00-211-2258

Electrical Receptacle Connector - Page 2 of 2



Included Contact Q	uantity:
--------------------	----------

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0