Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-211-2399

Body Style: Straight shape threaded **Overall Length:** 0.631 inches **Overall Diameter:** Between 1.146 inches and 1.167 inches **Environmental Protection:** Hermetic **Distance From Mounting Shoulder To Front Face:** 0.317 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 850.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Steel single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Cadmium



Included Contact Quantity: 26 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Solder flange mounted **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.026 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0