NSN 5935-00-213-6275

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-213-6275

Body Style: Straight shape **Overall Length:** 52.00 millimeters **Overall Height:** 19.00 millimeters **Overall Width:** 17.00 millimeters **Environmental Protection:** Corrosion resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 3.20 millimeters **Distance Between Mounting Facility Centers:** 46.00 millimeters **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping or silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:** 28 single mating end single contact grouping **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

NSN 5935-00-213-6275

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weig	ght:
----------------------------	------

0.028 gold grains, troy and 0.028 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0