## NSN 5935-00-213-6351

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-213-6351 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.718 inches **Overall Diameter:** 0.620 inches **Distance From Mounting Shoulder To Front Face:** 0.490 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** 

Plastic fluorocarbon single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** 

Copper alloy

## NSN 5935-00-213-6351

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Gold	
Included Contact Quantity:	
1 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round	
Included Contact Type:	
Coaxial socket single mating end single contact grouping	
Precious Material And Location:	
Contact and shell surfaces gold	
Precious Material And Weight:	
0.105 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A039b0	