NSN 5935-00-219-5447

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-219-5447

| view Online at https://aerobasegroup.com/nsn/5935-00-219-5447 |
|--|
| Thread Class: |
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Height: |
| 0.890 inches |
| Overall Width: |
| 1.141 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Distance Between Mounting Facility Centers: |
| 2.328 inches |
| Threaded Device Type: |
| Coupling facility and back shell |
| Mating End Quantity: |
| 12 |
| Contact Position Arrangement Style: |
| 26 single mating end |
| Polarization Method: |
| Jackscrew and polarization boss |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thread Size: |
| 0.138 inches and 0.138 inches and 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end |
| Shell Material: |
| Aluminum alloy or zinc |
| Shell Surface Treatment: |
| Anodize and dichromate potassium |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification |
| single material response single mating end |
| Special Features: |
| Item must comply with requirements of defense electronics supply center production standard no. L01184 |
| Thread Series Designator: |
| Unc and unc and unc |

N/a

Shelf Life:

NSN 5935-00-219-5447

Electrical Receptacle Connector Body - Page 2 of 2



| Demilitarization: | |
|-------------------|--|
| No | |
| Fiig: | |
| A039b0 | |

Unit Of Measure:

Mil-std (military Standard):

Mil-m-14 spec.