

View Online at <https://aerobasegroup.com/nsn/5935-00-220-2295>

**Body Style:**

Straight shape

**Overall Length:**

Between 1.198 inches and 1.228 inches

**Overall Height:**

Between 0.419 inches and 0.439 inches

**Overall Width:**

Between 0.479 inches and 0.509 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.110 inches and 0.130 inches

**Distance Between Mounting Facility Centers:**

Between 0.979 inches and 0.989 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

9 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

550.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14, type sdc-f military specification single material response single mating end

**Included Contact Quantity:**

9 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.