NSN 5935-00-220-6759

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-220-6759 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 0.820 inches **Overall Height:** 1.000 inches **Overall Width:** 2.625 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.468 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.280 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1200.0 single mating end single contact grouping **Connector Locking Method:** Screw lock pin **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Glass single mating end and plastic single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Included Contact Quantity:**

96 single mating end single contact grouping

NSN 5935-00-220-6759

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Hermaphrodite single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.096 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0