Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-221-3240

Thre	ead Class:
2b	
Thre	ead Direction:
Righ	nt-hand
Bod	ly Style:
Stra	ight shape, external coupling
Ove	erall Length:
Betv	ween 0.703 inches and 0.797 inches
Ove	erall Height:
Betv	veen 1.859 inches and 1.891 inches
Ove	erall Width:
Betv	veen 1.859 inches and 1.891 inches
Untl	hreaded Mounting Hole Diameter:
	ween 0.139 inches and 0.149 inches
Cen	ter To Center Distance Between Mounting Facilities Parallel To Height:
	veen 1.498 inches and 1.508 inches
Dist	ance Between Centerlines Of Mounting Facilities Parallel To Body Width:
	veen 1.498 inches and 1.508 inches
Dist	ance From Mounting Shoulder To Front Face:
Betv	ween 0.422 inches and 0.453 inches
Thre	eaded Device Type:
Cou	pling facility
Mati	ing End Quantity:
1	
Con	tact Position Arrangement Style:
Fk-1	0 single mating end
Con	tact Removability:
Non	removable single mating end all contact groupings
Con	tact Maximum Current Rating In Amps:
15.0) single mating end 1st contact grouping
Pola	arization Method:
Key	way or multiple keyway
Inse	ert Position In Deg:
0.0	
She	II Туре:
Solid	d
Con	nector Locking Method:
	rnally threaded coupling nut
	ead Size:
1.81	2 inches
Terr	ninal Location:
	k single mating end all contact groupings



Contact Material: Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 8 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.010 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Un Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0