# NSN 5935-00-222-7808

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-222-7808



# **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style: Overall Length:** 2.312 inches **Overall Diameter:** 1.719 inches Salt water resistant

Straight shape, internal coupling w/backshell

**Environmental Protection:** 

**Threaded Device Type:** 

Back shell and coupling facility

Mating End Quantity:

1

**Contact Position Arrangement Style:** 

24-7 single mating end

**Contact Maximum Current Rating In Amps:** 

41.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 single mating end 1st contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

0.0

Shell Type:

Split

**Connector Locking Method:** 

Internally threaded coupling nut

**Thread Length:** 

0.375 inches and 0.719 inches

**Thread Size:** 

1.438 inches and 1.500 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Surface Treatment:** 

Silver single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate single mating end

## NSN 5935-00-222-7808

Electrical Plug Connector - Page 2 of 2



#### Terminal Type:

Solder well single mating end all contact groupings

#### Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Chromate

### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

#### **Included Contact Quantity:**

2 single mating end 1st contact grouping

#### **Included Contact Type:**

Round pin single mating end all contact groupings

#### **Precious Material And Location:**

Contact surface silver

#### **Precious Material:**

Silver

#### **Test Data Document:**

81349-mil-c-5015-d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef and unef

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-m-14 spec.