NSN 5935-00-222-7888

Thread Class:

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-222-7888

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Diameter:
1.719 inches
Environmental Protection:
Moisture resistant and salt water resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
24-20 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Split
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Conduit nut
Thread Length:
0.375 inches and 0.625 inches
Thready Qty Per Inch (tpi):
18 and 12
Thread Size:
1.438 inches and 1.500 inches
Terminal Location:

NSN 5935-00-222-7888Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
9 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfacg gold
Precious Material:
Gold
Thread Series Designator:
Unef and unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.