NSN 5935-00-222-8064

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-222-8064

3
Body Style:
Straight shape
Overall Length:
1.485 inches
Overall Height:
0.365 inches
Overall Width:
0.215 inches
Environmental Protection:
Shock resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.089 inches and 0.094 inches
Distance Between Mounting Facility Centers:
Between 1.265 inches and 1.275 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response single mating end
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:

0.037 gold grains, troy

NSN 5935-00-222-8064

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-m-19833 spec.