NSN 5935-00-223-0674



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-223-0674 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 1.060 inches **Overall Height:** 1.730 inches **Overall Width:** 0.390 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Cable Entrance Diameter:** 0.220 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, top opening **Connector Locking Method:** Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thread Size:

0.099 inches and 0.099 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-223-0674Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0