NSN 5935-00-223-4382

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-223-4382 **Thread Class:** 2b and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.969 inches **Overall Height:** 1.062 inches **Overall Width:** 1.062 inches **Environmental Protection:** Explosion proof and pressure proof Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14s-2 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:**

Internally threaded shell

Thready Qty Per Inch (tpi):

40 and 32

NSN 5935-00-223-4382

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.112 inches and 0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Chromium single mating end single contact grouping and copper single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic silicone single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize and dichromate
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.004 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0