NSN 5935-00-223-8703

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-223-8703

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.099 inches and 1.119 inches

Overall Height:

Between 1.677 inches and 1.697 inches

Overall Width:

Between 3.365 inches and 3.385 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.870 inches and 2.880 inches

Distance From Mounting Shoulder To Front Face:

Between 0.146 inches and 0.166 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

32 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

40.0 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

10.0 all mating ends single contact grouping

Shell Type:

Solid

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

Terminal Type:

Solder well all mating ends single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Precious Material And Location:

Contact surface gold and contact surface silver

NSN 5935-00-223-8703

Electrical Receptacle Connector - Page 2 of 2



| | Precious | Material | And | Weight: |
|--|----------|----------|-----|---------|
|--|----------|----------|-----|---------|

0.160 gold grains, troy and 0.160 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0