## NSN 5935-00-224-5607

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-224-5607 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.250 inches **Overall Diameter:** 0.800 inches **Environmental Protection:** Moisture resistant and vibration resistant and vibration resistant **Mounting Facility Thickness:** Between 0.045 inches and 0.240 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Frequency Rating:** 4000.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Crimp single mating end single contact grouping

**Included Contact Quantity:** 

1 single mating end single contact grouping

## NSN 5935-00-224-5607

A039b0

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Item must comply with requirements of defense electronics supply center production standard no. L00104
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: