NSN 5935-00-224-6020

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-224-6020 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.160 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Environmental Protection:** Dust resistant and humidity resistant **Unthreaded Mounting Hole Diameter:** 0.190 inches **Center To Center Distance Between Mounting Facilities Parallel To Height: 1.317** inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.317 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 12 number 16 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 16.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 15.0 Shell Type: Solid **Connector Locking Method:**

16

Externally threaded shell Thready Qty Per Inch (tpi):

NSN 5935-00-224-6020

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.