NSN 5935-00-225-1599

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-225-1599 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.980 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches **Overall Height:** 1.140 inches **Overall Width:** 1.740 inches **Environmental Protection:** Watertight Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid Thread Length: 0.380 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:

Plastic polycarbonate single mating end

NSN 5935-00-225-1599

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|---|
| Crimp and solder single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Insert Material Specification: |
| Naval specification os 12531 mfr ref single material response single mating end |
| Included Contact Quantity: |
| 132 single mating end single contact grouping |
| Included Contact Type: |
| Square button single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.132 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |