## NSN 5935-00-225-8962

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-225-8962

**Body Style:** Pcb, angle shape, external coupling **Overall Length:** 0.620 inches **Overall Height:** 0.500 inches **Overall Width:** 0.312 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 1000.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-626, comp 22, 1/2 hard federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Gold

# NSN 5935-00-225-8962

Electrical Receptacle Connector - Page 2 of 2



### **Included Contact Quantity:**

1 single mating end single contact grouping

#### **Included Contact Type:**

Coaxial socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact and body surfaces gold

#### **Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0