# NSN 5935-00-225-9656

Electrical Plug Connector - Page 1 of 2



V	iew Online at https://aerobasegroup.com/nsn/5935-00-225-9656
В	ody Style:
Н	lood, top opening w/clamp
0	overall Length:
1.	.000 inches
0	overall Height:
1.	.234 inches
0	Overall Width:
0.	.406 inches
С	able Entrance Diameter:
В	etween 0.344 inches and 0.500 inches
M	lating End Quantity:
1	
С	contact Position Arrangement Style:
14	4 single mating end
С	contact Removability:
Ν	lonremovable single mating end single contact grouping
С	ontact Maximum Current Rating In Amps:
7.	.5 single mating end single contact grouping
Ρ	olarization Method:
G	Guide pin/socket
s	hell Type:
Н	lood, top opening
С	connector Cable Strain Relief Method:
С	Sable clamp
T	erminal Location:
В	ack single mating end single contact grouping
С	Contact Material:
С	copper alloy single mating end single contact grouping
С	Contact Surface Treatment:
G	old single mating end single contact grouping
In	nsert Material:
Р	lastic diallyl phthalate single mating end

## **Terminal Type:**

Solder well single mating end single contact grouping

### **Shell Material:**

Aluminum alloy

### **Shell Surface Treatment:**

Anodize

### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

### **Included Contact Quantity:**

14 single mating end single contact grouping

# NSN 5935-00-225-9656

Electrical Plug Connector - Page 2 of 2



# Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surface gold Precious Material And Weight: 0.014 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Mil-std (military Standard):

Mil-m-14 spec.

Fiig: A039b0