

View Online at <https://aerobasegroup.com/nsn/5935-00-225-9873>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

4.360 inches

**Overall Height:**

0.790 inches

**Overall Width:**

0.406 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and shock proof and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Distance Between Mounting Facility Centers:**

4.046 inches

**Board Accommodated Length:**

3.593 inches single board

**Board Accommodated Width:**

Between 0.080 inches and 0.104 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Pin single mating end single contact grouping

**Insert Material Specification:**

Mil-m-19833 type gdi 30 military specification single material response single mating end

**Included Contact Quantity:**

44 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contacts and solder lugs surfaces gold

**Precious Material And Weight:**

0.044 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-19833 spec.