NSN 5935-00-226-3832

Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-226-3832

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
Between 2.001 inches and 2.063 inches
Overall Diameter:
2.214 inches
Environmental Protection:
Pressure proof and moisture resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
32-7 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 3rd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end 3rd contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end 3rd contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Length:
0.562 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
2.000 inches
Terminal Location:
Back single mating end all contact groupings

NSN 5935-00-226-3832

Electrical Plug Connector - Page 2 of 2



Contact Material: Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 7 single mating end 3rd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.175 gold grains, troy and 0.175 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-r-3065 spec.