Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-227-5153

Body Style:

Straight shape, external coupling strain relief

Overall Height:

43.300 millimeters

Overall Width:

43.300 millimeters

Body Length:

81.200 millimeters

Environmental Protection:

Waterproof

Unthreaded Mounting Hole Diameter:

3.750 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

36.9 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

36.900 millimeters

Cable Entrance Diameter:

25.400 millimeters

Distance From Mounting Shoulder To Front Face:

15.700 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

22-48 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

750.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-227-5153

Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Nickel single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end and glass single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 48 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0