NSN 5935-00-227-8402

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-227-8402

Thread Class: 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Diameter:** 1.719 inches **Environmental Protection:** Pressure proof and salt water resistant and vibration resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-20 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Split **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Conduit nut **Thread Length:** 0.375 inches and 0.625 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.438 inches and 1.500 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-00-227-8402Electrical Plug Connector - Page 2 of 2



| Contact Surface Treatment: |
|--|
| Silver single mating end all contact groupings |
| Insert Material: |
| Plastic melamine single mating end |
| Terminal Type: |
| Solder well single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Insert Material Specification: |
| Mil-m-14 military specification all material responses single mating end |
| Included Contact Quantity: |
| 9 single mating end 1st contact grouping |
| Included Contact Type: |
| Round pin single mating end all contact groupings |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.055 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Unef and unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-m-14 spec. |
| |