Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-227-8493

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.938 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Unthreaded Mounting Hole Diameter:
0.173 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.750 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
32-17 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
35.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

18

#### **Thread Size:**

2.000 inches

# **Terminal Location:**

Back single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Aluminum alloy

# **Included Contact Quantity:**

4 single mating end single contact grouping

# Included Contact Type:

Round socket single mating end single contact grouping

# **Thread Series Designator:**

Uns

Shelf Life:

N/a

--

#### Unit Of Measure:

Demilitarization:

No

Fiig:

. . . . .

A039b0